



## XF-PTL06516-C

### Specification

Optical structure	Bi-Telecentric
Magnification	0.248
Object field of view	$\phi 65.3\text{mm}$
Image field of view	$\phi 16.2\text{mm}$
Working Distance	160mm $\pm$ 3%
Telecentricity	$<0.03^\circ$ (0.09 $^\circ$ )
Depth of field	11.6mm
F#	F6.5
Resolution	17.3 $\mu\text{m}$
MTF	$>0.3@160\text{lp/mm}$
Distortion	$<0.017\%$ (0.080%)

Detector type:		
1'	12.8 $\times$ 9.6	51.6 $\times$ 38.7mm
2/3'	8.45 $\times$ 7.07	34.1 $\times$ 28.5mm
1/1.8'	7.2 $\times$ 5.3	29.0 $\times$ 21.4mm
1/2'	6.4 $\times$ 4.8	25.8 $\times$ 19.4mm

### XF-PTLAAABB-C/F/P/M- (L90E)

The fourth generation lens of Canrill

Object FOV

Image FOV

The camera mount (M & P mount need specify BFL)

90° Steering option

Undefined tolerance (mm)	degree	File Name		
X. X	$\pm 0.2$	$\pm 30\text{min}$	XF-PTL06516-C-外形尺寸-EN	
X. XX	$\pm 0.02$	Drawing Name		
X. XXX	$\pm 0.005$	Drawing Size: A3		
	Sign	Data/Ver.	Material	Ratio
Design				1:5
Modify1			Qty	
Modify2			Total:	Page:
				Canrill OPTICS
				All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.