



XF-PTL06562-M72-11.48-VI

Specification

Optical structure	Bi-Telecentric
Magnification	0.989
Object field of view	Φ62.7mm
Image field of view	Φ62mm
Working Distance	160mm±3%
Telecentricity	<0.03°(0.09°)
Depth of field	1.2mm@F11
F#	F6-F83
Resolution	7.40μm@F11
MTF	>0.3@95lp/mm@F11
Distortion	<0.037%(0.10%)
Detector type:	

35film 36×24	36.4×24.3mm
2' 23×23	23.3×23.3mm
4/3' 18×13.5	18.2×13.7mm
1.1' 14.2×10.4	14.4×10.5mm
4K Linear scan 4096×7μm	29.0mm
8K Linear scan 8192×5μm	41.4mm
8K Linear scan 8192×7μm	58.0mm
12K Linear scan 12288×5μm	62.1mm

Optional camera mount:
 1、M58×0.75
 2、M72×0.75

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p>90° Steering option</p>
--	---

Undefined tolerance (mm)		degree	File Name		
X. X	±0.2	±30min	XF-PTL06562-M72-11.48-VI-外形尺寸-EN		
X. XX	±0.02		Drawing Name		
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.