



XF-PTL09244-M58-11.48-VI

- Optional camera mount**
- 1、 F
 - 2、 M58×0.75
 - 3、 M42×1

Specification

Optical structure	Bi-Telecentric
Magnification	0.486
Object field of view	Φ89.7mm
Image field of view	Φ43.6mm
Working Distance	250mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	4.1-27.1mm
F#	F9-F57
Resolution	12.2-77.7μm
MTF	>0.3@115-18lp/mm
Distortion	<0.050%(0.100%)
Detector type:	
35film 36×24	74.1×49.4mm
2' 23×23	47.3×47.3mm
4/3' 18×13.5	37.0×27.8mm
1.1' 14.2×10.4	29.2×21.4mm
2K Linear scan 2048×10μm	42.1mm
4K Linear scan 4096×7μm	59mm
8K Linear scan 8192×5μm	84.3mm

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p style="text-align: right;">90° Steering option</p>
--	--

Undefined tolerance (mm)	degree	File Name		
X. X	±0.2	±30min	XF-PTL09244-M58-11.48-VI-外形尺寸-EN	
X. XX	±0.02	Drawing Name		
X. XXX	±0.005	Drawing Size: A3		
	Sign	Data/Ver.	Material	Ratio
Design				1:5
Modify1			Qty	☐ ⊕
Modify2			Total:	Page:

CAN RILL OPTICS

All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.