



XF-PTL13757-M72-11.48-VI

Optional camera mount
 1、 M58×0.75
 2、 M72×0.75

Specification

Optical structure	Bi-Telecentric
Magnification	0.433
Object field of view	Φ132.6mm
Image field of view	Φ57.4mm
Working Distance	280mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	6.4mm@F11
F#	F6-F76
Resolution	16.8μm@F11
MTF	>0.3@95lp/mm@F11
Distortion	<0.034%(0.067%)
Detector type:	
35film 36×24	83.1×55.4mm
2' 23×23	53.1×53.1mm
4/3' 18×13.5	41.6×31.2mm
1.1' 14.2×10.4	32.8×24.0mm
2K Linear scan 2048×10μm	47.3mm
4K Linear scan 4096×7μm	66.2mm
8K Linear scan 8192×5μm	94.6mm
8K Linear scan 8192×7μm	132.4mm

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV</p> <p>Image FOV</p>	<p>The camera mount (M & P mount need specify BFL)</p>	<p>90° Steering option</p>
--	---	-----------------------------------

Undefined tolerance (mm)		degree	File Name		
X. X	±0.2	±30min	XF-PTL13757-M72-11.48-VI-外形尺寸-EN		
X. XX	±0.02		Drawing Name		
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.