



XF-PTL23835-F

Optional camera mount

- 1、 F mount
- 2、 M42×1

Specification

Optical structure	Bi-Telecentric
Magnification	0.152
Object field of view	Φ230.3mm
Image field of view	Φ35mm
Working Distance	410mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	35.4mm
F#	F7.5
Resolution	32.5μm
MTF	>0.3@140lp/mm
Distortion	<0.030%(0.053%)
Detector type:	

2'	23×23	151.3×151.3mm
4/3'	18×13.5	118.4×88.8mm
1.1'	14.2×10.4	93.4×68.4mm
1'	12.8×9.6	84.2×63.2mm
2K	Linear scan 2048×10μm	134.7mm
4K	Linear scan 4096×7μm	188.6mm

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p style="text-align: right;">90° Steering option</p>
--	--

Undefined tolerance (mm)		degree	File Name		
X. X	±0.2	±30min	XF-PTL23835-F-外形尺寸-EN		
X. XX	±0.02		Drawing Name		
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.