



XF-PTL35057-M72-11.48-VI

Optional camera mount
 1、 M58×0.75
 2、 M72×0.75

Specification

Optical structure	Bi-Telecentric
Magnification	0.17
Object field of view	$\phi 337.6\text{mm}$
Image field of view	$\phi 57.4\text{mm}$
Working Distance	$540\text{mm} \pm 3\%$
Telecentricity	$< 0.05^\circ (0.06^\circ)$
Depth of field	$41.7\text{mm} @ F11$
F#	F6-F76
Resolution	$42.8\mu\text{m} @ F11$
MTF	$> 0.3 @ 95\text{lp/mm} @ F11$
Distortion	$< 0.026\% (0.052\%)$
Detector type:	

35film 36×24	211.8×141.2mm
2' 23×23	135.3×135.3mm
4/3' 18×13.5	105.9×79.4mm
1.1' 14.2×10.4	83.5×61.2mm
2K Linear scan 2048×10μm	120.5mm
4K Linear scan 4096×7μm	168.7mm
8K Linear scan 8192×5μm	240.9mm
8K Linear scan 8192×7μm	337.3mm

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV</p> <p>Image FOV</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p>90° Steering option</p>
---	---

Undefined tolerance (mm)		degree	File Name		
X. X	±0.2	±30min	XF-PTL35057-M72-11.48-VI-外形尺寸-EN		
X. XX	±0.02		Drawing Name		
X. XXX	±0.005	Drawing Size: A3			
	Sign	Data/Ver.	Material	Ratio	Product Name
Design				1:5	
Modify1			Qty		Canrill OPTICS
Modify2			Total:	Page:	All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.